

RedWind 2017 (20m 4-Doors)

This simple product solves a number of minor issues by sealing the area around the doors:

- Prevents air leakage to maintain integrity of the air-conditioning
- Prevents dust from being sucked into the car
- Prevents whistling noises caused by air leakage around the door
- Improves the door shutting sound, making it sound softer
- Prevents airborne noise from entering the saloon



MATERIAL DATA SHEET

Name of index	Value	Testing method
Package Dimension (W*L*H) (cm)	15.0*15.0*7.0	
Package weight (kg,avg)	0.48 +-10%	
Package volume (m ³ ,avg)	0.0015 +-10%	

PROPERTIES

We have included a wire inside RedWind to ensure it doesn't tear when pulling through the door seals, to save your time and effort. RedWind has increased internal elasticity to ensure the longevity and high efficiency of this product even when it is stretched.

COMPOSITION

Kauchuk rubber tube with wire inside

APPLICATION

Recommended usage areas: Inside OEM rubber tubing around the door

1. Remove car door seal
2. Take steel wire (or plastic cord), lubricate it with soap or shampoo to ease insertion
3. Tie an end of the wire or cord to RedWind and pull it through the seal.
4. If seal has no openings, make a small (up to 10mm) incision, after inserting RedWind glue the openings shut

PACKING TYPE / LENGTH

Box-20m / 20.0 m

IATF 16949:2016
ISO 14001:2015



SGS



www.drartex.com/products